

DrillNow™

UH-2 Drill-Through Wellhead

Delivering Superior Service. Wellhead experts since 1930

Realize increased reliability and productive time on the pad with our Slim Bore Shale Unihead (UH-2) system.

The UH-2 was developed to bring the benefits of Unihead technology to shale applications. The UH-2 features our standard hanger and lock ring packoff technology increasing productive time and enhancing safety on the pad. The UH-2 is optimized for Surface x Intermediate x Production Casing well designs and utilizes our standard Unihead production casing hangers and packoffs ensuring availability and improving operational reliability.




Speed

- ▶ Saves up to 30 hours of rig time
- ▶ SWC BOP Quick Connect available
- ▶ Offline Cementing, every string
- ▶ Offline BOP testing




Operational Performance

- ▶ Field proven performance
- ▶ Internal Lock Ring hanger retention
- ▶ Independent load shoulders
- ▶ Detailed installation procedures
- ▶ Experienced service personnel



Versatility

- ▶ Installation through riser or rotary table
- ▶ Ability to rotate production casing hanger
- ▶ Drill for liner without BOP break



Applications

- ▶ 11" BOP
- ▶ Surface Casing- 8 5/8" - 10 3/4"
- ▶ Intermediate Casing - 7" - 7 5/8"
- ▶ Production Casing- 4 1/2" - 6"
- ▶ Drilling Pressures- 5K & 10K
- ▶ Completion Pressures- 10K & 15K



Safety

- ▶ Eliminates work below suspended loads
- ▶ Reduced wellhead penetrations
- ▶ BPV profile on production hanger
- ▶ Reduced time in cellar

➤ To purchase or get more information, contact your TechnipFMC sales representative or email infoSA@TechnipFMC.com

TechnipFMC
13460 Lockwood Rd.
Houston, Texas 77044 USA
Tel.: +1 281 591 4000

TechnipFMC.com